

SAGA-DAN



Windrower

- ★ Windrowers in 2.5, 3, 4 and 5 metre width.
- ★ Model 10: with welded teeth to rake small stones.
Model 15: with changeable teeth to rake max. depth.
- ★ Windrowers all mounted in the three point hitch.
- ★ Windrowers with strong and efficient transmission.
- ★ Windrowers with single or doublewheel.
- ★ Windrowers with fixed or turnable wheel.
- ★ Windrowers for the best work in the field.



SAGA-DAN

Saga-Dan Windrower with the depending details

Transmission buildt to be used

Transmission from tractor to windrower via a strong reductionsgear and secured by a Walterscheid clutch.

Easy maintenance and service

The rotor is driven by a heavy-duty chain with a few wearing parts.
Fast and secure adjustments.

Make the right choice for your job

SAGA-DAN windrower can be equipped with two models of rotors.
Model 10 has welded teeth and makes a perfect surface free of stones. Rakes stones down to 25 mm in size.
Model 15 has changeable teeth and rakes deep in the soil and takes the stones out and put them in a windrow.

Special feature

SAGA-DAN windrower can be fitted with rubberguards on the frame to align the windrow.



TECHNICAL DETAILS:

Model	Depth	Workingwidth	Capacity (3,5 km/h)	Power
SR 2515	0-10 cm	190 cm	0,54 ha	40 hp
SR 3010	0-10 cm	240 cm	0,85 ha	45 hp
SR 3015	0-15 cm	240 cm	0,85 ha	45 hp
SR 4010	0-15 cm	340 cm	1,20 ha	60 hp
SR 4015	0-15 cm	340 cm	1,20 ha	60 hp
SR 5015	0-15 cm	440 cm	1,60 ha	90 hp

SPECIFICATION CAN CHANGE WITHOUT FURTHER NOTICE

PRODUCTION/SALE



C. HAVEMOSE
MASKINFABRIK ApS
Svoldrupvej 18
DK-9640 Farsø
Telefon +45 98 63 15 22
Telefax +45 98 63 25 32
www.saga-dan.dk